

# Architectural Abstract

## Vinylrock® II, Vinylrock® X GYPSUM BASED CEILING


- Vinyl faced gypsum core.
- Appropriate for use in ceilings that require repeated cleaning.
- Meets USDA/FSIS sanitary standards for food processing, food service and hospital use.
- Vinylrock® X panels are Fire Rated BPB ProRoc™ Type C Gypsum Board for installation in specific UL fire resistive designs.
- Vinylrock® II panels are lighter weight and easier to install.



Item Number	Nominal Size (Inches)	Edge Detail	NRC	CAC	LR	Sq. Ft. Per Carton
<b>Safetone® Class A</b>						
<b>Vinylrock® II – White CRF</b>						
1132-CRF-1	24 x 24 x 1/4	Trim	–	35	.88	32
1130-CRF-1	24 x 48 x 1/4	Trim	–	35	.88	32
<b>Safetone® Class A</b>						
<b>Vinylrock® II – White Plume</b>						
1132-PLM-1	24 x 24 x 1/4	Trim	–	35	.85	32
1130-PLM-1	24 x 48 x 1/4	Trim	–	35	.85	32
<b>Protectone® (For specific UL fire resistance time-rated assemblies)</b>						
<b>Vinylrock® X – White CRF</b>						
1142-CRF-1	24 x 24 x 1/2	Trim	–	40	.88	32
1140-CRF-1	24 x 48 x 1/2	Trim	–	40	.88	32
<b>Protectone® (For specific UL fire resistance time-rated assemblies)</b>						
<b>Vinylrock® X – White Plume</b>						
1142-PLM-1SV	24 x 24 x 1/2	Trim	–	40	.85	32
1140-PLM-1SV	24 x 48 x 1/2	Trim	–	40	.85	32

ASTM E 1264 Classification: Type XX, Pattern G

### Edge Detail



**Trim Edge**  
(Square) 1/16" Grid

### Popular Applications:

- Bank Drive-thru Canopies • Hospitals
- Parking Garages • Food Processing

### Finishes



White CRF  
CRF-1



White Plume  
PLM-1



# PRODUCT SPECIFICATION DETAILS

## ACOUSTICAL CEILING SYSTEMS

### 09500

#### PART 2: PRODUCTS

##### 2.1 GENERAL

Provide acoustical ceiling material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

##### 2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XX (gypsum base)
2. Form NA
3. Pattern G
4. Gypsum lay-in panel with vinyl finish [White CRF] [White Plume]
5. Size Vinylrock® X- 1/2" x [24" x 24"] [24" x 48"]  
Vinylrock® II-1/4" x [24" x 24"] [24" x 48"]
6. Edge Detail Square (Trim)
7. Noise Reduction Coefficient (NRC) NA
8. Ceiling Attenuation Class (CAC) [35] [40]
9. Light Reflectance Coefficient (LR) [.85] [.88]  
Light Reflectance Designation LR-1
10. Color: White
11. Flame Spread Classification Class A
12. Underwriters Laboratories Inc. Fire Resistance Time-Rated Assembly\*  
[G222] [G259]
13. Manufacturer, subject to compliance with requirements of this specification, BPB
14. Product Name Capaul® Brand Vinylrock® [X] [II]

##### Size Options

24" x 24"

24" x 48"

\* Relavent to Vinylrock X only. Refer to UL Fire Resistance Directory for specific design information.

Distributed by:

#### USA

**BPB America Inc.**  
5301 West Cypress St., Suite 300  
Tampa, FL 33607  
Toll Free: +1-866-427-2872  
Fax: +1-800-829-1422  
E-mail: [crc@bpb-na.com](mailto:crc@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

#### Canada

**BPB Canada Inc.**  
Architectural Products Sales Division  
6715 Ogdendale Road SE  
Calgary, Alberta T2C 2A4  
Toll Free: +1-866-427-2872  
Fax: +1-800-829-1422  
E-mail: [crc@bpb-na.com](mailto:crc@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

#### Outside North America

**BPB America Inc.**  
5301 West Cypress St., Suite 300  
Tampa, FL 33607  
Phone: +1-813-286-3900  
Fax: +1-813-286-3908  
E-mail: [international@bpb-na.com](mailto:international@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

®™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-3996 Rev. B/5M/0605

