

CIRRUS® Open Plan

Square Lay-in & Tegular
fine texture



Cirrus Open Plan with Silhouette® 9/16" Bolt-Slot 1/4" reveal grid; Axiom® Classic Trim

Key Selection Attributes

- Excellent solution in mixed (open plan/closed plan) office design
- Excellent combination of acoustical performance; Articulation Class (180), NRC (0.75) and CAC 35
- 30-Year Limited System Warranty against visible sag (excludes items 551, 565, 568), mold/mildew and bacterial growth


Typical Applications

- Open plan offices
- Healthcare – assists in addressing HIPAA requirements
- Libraries/media centers
- Lobbies/reception areas
- Computer rooms

Detail



CIRRUS Open Plan
Beveled Tegular



CIRRUS Open Plan with
SILHOUETTE® 9/16"
Bolt-Slot 1/4" reveal grid

Color



White (WH)



CIRRUS® Open Plan

Square Lay-in & Tegular
fine texture

Recycled Content: **73%**

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	LEED for Schools	
✓	✓	✓	✓	✓	✓	Acoustics	Low Emitting or CHPS
			Location Dependent			✓	✓

\$\$\$\$\$

Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Item No.	Acoustics Dimensions	UL Classified	Fire			Light Rating	Sag Reflect	Anti-Resist	VOC Microbial	Durable Formaldehyde	Recycle	Program
				NRC	AC	CAC							
9/16" Beveled Tegular	558	2' x 2' x 7/8"	☐	0.75	180	35	Class A	0.85	HumiGuard+	BioBlock+	No Added	S	Yes
	558M	600 x 600 x 22mm		•	•	•							
15/16" Angled Tegular	568	2' x 4' x 7/8"	☐	0.75	180	35	Class A	0.85	S	•	No Added	S	•
	568M	600 x 1200 x 22mm		•	•	•							
Square Lay-in	563	2' x 2' x 7/8"	☐	0.75	180	35	Class A	0.85	•	•	No Added	S	•
	563M	600 x 600 x 22mm		•	•	•							
Square Lay-in	565	2' x 4' x 7/8"	☐	0.75	180	35	Class A	0.85	S	•	No Added	S	•
	565M	600 x 1200 x 22mm		•	•	•							

S = Standard

Suspension Systems

9/16"	Standard: Interlude®, Silhouette® Bolt-Slot, Sonata™, Suprafine®, Trimlok® Screw-Slot
15/16"	Standard: Prelude®

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Type III, Form 1, Pattern E I C
Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

No-Added Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 2.3 (BTU units)
R Factor – 0.40 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information

See warranty details at armstrong.com/warranty

Application Considerations

Not recommended for rooms containing MRI equipment

Weight: Square Feet/Carton

551, 565, 568 – 1.21 lbs/SF; 48 SF/ctn
556, 558 – 1.40 lbs/SF; 40 SF/ctn
563 – 1.33 lbs/SF; 40 SF/ctn

TechLineSM / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: cirrus)
CS-3043-109

© AWI Licensing Company, 2009 • Printed in the United States of America

