

CIRRUS® Profiles

Beaded, Chamfered, Beveled & Classic Step

Tegular fine texture



Cirrus Beaded with Suprafine® 9/16" Exposed grid



Cirrus Beaded Scored with Suprafine 9/16" Exposed Tee grid



Cirrus Classic Step with Suprafine 9/16" Exposed Tee grid

Key Selection Attributes

- Classic edge details on Cirrus refined texture
- Excellent sound absorption
- 30-Year Limited System Warranty against visible sag (excludes items 562, 585, 590, 626), mold/mildew and bacterial growth
- Hardware Friendly Options are available (noted with a 1), providing precut finished edge details for fixture openings (1" to 16" diameter)

Typical Applications

- Offices
- Healthcare – assists in addressing HIPAA requirements
- Conference rooms
- Lobbies/reception areas
- Public spaces/areas


Detail




CIRRUS Beaded




CIRRUS Chamfered



CIRRUS Beaded with SUPRAFINE 9/16" Exposed Tee grid



CIRRUS Classic Step with SUPRAFINE 9/16" Exposed Tee grid



Hardware Friendly Options Available

Color



White (WH)

CIRRUS® Profiles

Beaded, Chamfered, Beveled & Classic Step
Tegular fine texture

Recycled Content: 65-83%

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓		✓
Location Dependent							

\$\$\$\$\$

Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program	
			Acoustics NRC	CAC								
CIRRUS Profiles Beaded*												
	561 [†] 561M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.65	35	Class A	0.86	HumiGuard+	BioBlock+	No Added	S	Yes
	562 [†] 562M	2' x 2' x 3/4" 600 x 600 x 19mm	▣	0.65	35	Class A	0.86	S		No Added	S	
	623 [†] 623M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.65	35	Class A	0.86			No Added	S	
	CIRRUS Profiles Chamfered*											
	557 [†] 557M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.65	35	Class A	0.86			No Added	S	
		628 [†] 628M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.65	35	Class A	0.86			No Added	S
CIRRUS Profiles Beveled												
	590 [†] 590M	2' x 2' x 3/4" 600 x 600 x 19mm	▣	0.65	35	Class A	0.86	S		No Added	S	
CIRRUS Profiles Classic Step												
	591 [†] 591M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.65	35	Class A	0.86			No Added	S	
	585 [†] 585M	2' x 2' x 3/4" 600 x 600 x 19mm	▣	0.65	35	Class A	0.86	S		No Added	S	
	591 [†] 591M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.65	35	Class A	0.86			No Added	S	
	626 [†] 626M	2' x 2' x 3/4" 600 x 600 x 19mm	▣	0.65	35	Class A	0.86	S		No Added	S	

S = Standard
[†] Available with Hardware Friendly Options (U.S. Patent 5,231,810)
 * Ceiling design copyrighted by AWI Licensing Co.

Suspension Systems

9/16"	Standard: Suprafine®
15/16"	Standard: Prelude®

Physical Data

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
557, 561, 591, 623, 628 – Type III, Form 1, Pattern E I
562, 585, 590, 626 – Type III, Form 1, Pattern E I K
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

No-Added Formaldehyde
No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

Anti Mold/Mildew & Bacteria
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value
R Factor – 1.9 (BTU units)
R Factor – 0.33 (Watts units)

Backloading Recommendation
Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information
See warranty details at armstrong.com/warranty

Application Considerations
Not recommended for rooms containing MRI equipment

Weight; Square Feet/Carton
561, 590, 591 – 1.06 lbs/SF; 48 SF/ctn
557, 562, 585, 623, 626, 628 – 1.17 lbs/SF; 48 SF/ctn

TechLineSM / 1 877 ARMSTRONG
1 877 276 7876
armstrong.com/ceilings (search: cirrus)
CS-4016-109

© AWI Licensing Company, 2009 • Printed in the United States of America

