

CORTEGA® Second Look®

Scored Tegular
medium texture



Cortega Second Look II with Suprafine® 9/16" Exposed Tee grid

Key Selection Attributes

- Geometric scored visuals
- Economical

Typical Applications

- Many types of commercial interiors
- Department stores/retail

Face View Photos



Second Look I scoring creates nominal 12" x 12" squares



Second Look II scoring creates nominal 24" x 24" squares

Detail



CORTEGA Second Look Squares



CORTEGA Second Look with SUPRAFINE 9/16" Exposed Tee grid

Color



White (WH)

CORTEGA® Second Look®

Scored Tegular
medium texture

Recycled Content: 26-38% Fire Guard 51%







LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	LEED for Schools	
✓	✓	✓	✓	✓		Acoustics	Low Emitting or CHPS
			Location Dependent				✓

\$\$\$\$\$

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified Acoustics NRC CAC	Fire Rating CAC	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program	
											UL Classified
CORTEGA Second Look I											
15/16" Angled Tegular 	2765	2' x 4' x 3/4"		0.55 35	Class A	0.82	S	-	Low	S	Yes
	2765M	600 x 1200 x 19mm									
CORTEGA Second Look II											
9/16" Angled Tegular 	2776	2' x 4' x 3/4"		0.55 30	Class A	0.82	S	-	Low	S	•
15/16" Angled Tegular 	2758	2' x 4' x 3/4"		0.55 40	Fire Guard	0.82	S	-	No Added	S	•
	2767	2' x 4' x 3/4"		0.55 35	Class A	0.82	S	-	Low	S	•
	2767M	600 x 1200 x 19mm		0.55 35	Class A	0.82	S	-	No Added	S	•
	2767NF	2' x 4' x 3/4"		0.55 35	Class A	0.82	S	-	No Added	S	•

S = Standard

Suspension Systems

9/16"	Standard: Suprafine®
15/16"	Standard: Prelude®
	Fire Guard™: Prelude XL Fire Guard

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification

Type III Form 2, Pattern C D K
Fire Class A

No-Added/Low Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

Low Formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

Warranty Information

See warranty details at armstrong.com/warranty

Weight: Square Feet/Carton

2765, 2767, 2776 – 0.70 lbs/SF; 80 SF/ctn
2758 – 1.20 lbs/SF; 64 SF/ctn

TechLine™ / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: cortega)
CS-3022-109

© AWI Licensing Company, 2009 • Printed in the United States of America

