

DESIGNER Angled Tegular with PRELUDE® 15/16" Exposed Tee grid

Visua		Performance Selection Dots represent highest level of performance.										
Grid Face	Edge Profile	ltem Number	Dimensions	UL Cla Acou NRC	issified Istics CAC	Fire Rating	Light Reflect	Sag Resist	Anti- Microbial	VOC Formaldehyde	Recycling Program	Durable
DESIGN	ER											
15/16″	Square Lay-in	735	2' x 2' x 5/8"	0.55	30	Class A	0.81	S	-	Low	Yes	S
		734	2' x 4' x 5/8"	0.55	30	Class A	0.81	S	-	Low	•	S
5	Angled Tegular	737	2' x 2' x 5/8"	0.55	33	Class A	0.81	S	-	Low	•	S

S = Standard

Physical Data

Material Wet-formed mineral fiber

Surface Finish Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification 734, 735, 737 -Type III, Form 2, Pattern F, Fire Class A

Insulation Value 734, 735, 737 -R Factor - 1.5 (BTU units)

R Factor - 0.26 (Watts units) Low Formaldehyde Low Formaldehyde - contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other

building types in CHPS Section 01350. Backloading

Recommendation Contact TechLine for specific information

Weight; Square Feet/Carton

734 - 0.80 lbs/SF; 80 SF/ctn 735, 737 - 0.80 lbs/SF; 64 SF/ctn

Warranty 1-year limited warranty. Details: armstrong.com/ceilings

Recommended Suspension System

Items	Suspension System
734, 735, 737	15/16" PRELUDE®



TechLine^{s™} / 1 877 ARMSTRONG 1 877 276 7876 armstrong.com/ceilings (search: designer) CS-3024-208