

DUNE™

Tegular
fine texture



Items 1774, 1775 & 1776



Dune with Interlude® 9/16" Dimensional Tee grid; Axiom® Classic Trim

Key Selection Attributes

- Upgrade look at a modest price
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth
- Durable
Scratch-resistant
- Non-directional visual reduces installation time and scrap

Typical Applications

- Offices
- Corridors
- Retail
- Hospitality
- Classrooms


Detail




DUNE



DUNE Tegular with SUPRAFINE® 9/16" Exposed Tee grid



DUNE Tegular with INTERLUDE XL 9/16" Dimensional Tee grid



DUNE Tegular with SILHOUETTE® 9/16" Bolt-Slot grid 1/4" Reveal

Color



White (WH)



Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓		✓
Location Dependent							



Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program	
			Acoustics NRC	CAC								
DUNE Tegular 9/16" Beveled Tegular 	1775	2' x 2' x 5/8"	□	0.50	35♦	Class A	0.83	HumiGuard+	BioBlock+	Low	Scratch	Yes
	1775M	600 x 600 x 15mm										
	1775NF	2' x 2' x 5/8"		0.50	35♦	Class A	0.83			No Added		
	1852	2' x 2' x 5/8"	□	0.50	35	Fire Guard	0.83			Low		
	1777	2' x 4' x 5/8"	□	0.50	35	Class A	0.83			Low		
	1777M	600 x 1200 x 15mm										
15/16" Angled Tegular 	1774	2' x 2' x 5/8"	□	0.50	35	Class A	0.83			Low		
	1774M	600 x 600 x 15mm										
	1774NF	2' x 2' x 5/8"		0.50	35	Class A	0.83			No Added		
	1853	2' x 2' x 5/8"	□	0.50	35	Fire Guard	0.83			Low		
	1776	2' x 4' x 5/8"	□	0.50	35	Class A	0.83			Low		
	1776M	600 x 1200 x 15mm										

♦ 1775-CAC 33 on 9/16" Interlude, Sonata, Suprafine

Suspension Systems

9/16"	Standard: Interlude®, Silhouette® Bolt-Slot, Sonata™, Suprafine®, Trimlok® Screw-Slot	Fire Guard™: Suprafine XL Fire Guard
15/16"	Standard: Prelude®	Fire Guard: Prelude XL Fire Guard

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)
Fire Guard: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification

Type III, Form 2, Pattern C E
Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

No-Added/Low Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

Low formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information

See warranty details at armstrong.com/warranty

Weight; Square Feet/Carton

1774, 1775 – 0.75 lbs/SF; 64 SF/ctn
1776, 1777 – 0.75 lbs/SF; 80 SF/ctn
1852, 1853 – 1.20 lbs/SF; 48 SF/ctn

DUNE™

Square Lay-in
fine texture



Items 1772, 1773



Dune with Prelude® XL 15/16" Exposed Tee grid; Axiom® Classic Trim

Key Selection Attributes

- Upgrade look at a modest price
- 30-Year Limited System Warranty against visible sag (excludes items 1796 and 1798), mold/mildew and bacterial growth
- Durable
Scratch-resistant
- Non-directional visual reduces installation time and scrap

Typical Applications

- Offices
- Corridors
- Retail
- Hospitality
- Classrooms

Detail



DUNE



DUNE Square Lay-in
with PRELUDE 15/16"
Exposed Tee grid

Color



White (WH)



Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓		✓
Location Dependent							



Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program	
			Acoustics NRC	CAC								
DUNE Square Lay-in												
15/16" Square Lay-in 	1772	2' x 2' x 5/8"	□	0.50	30	Class A	0.83	HumiGuard+	BioBlock+	Low	Scratch	Yes
	1772M	600 x 600 x 15mm					•	•	•		•	•
	1772NF	2' x 2' x 5/8"		0.50	30	Class A	0.83	•	•	No Added	•	•
	1850	2' x 2' x 5/8"	□	0.50	35	Fire Guard	0.83	•	•	Low	•	•
	1850M	600 x 600 x 15mm						•	•		•	•
	1773	2' x 4' x 5/8"	▭	0.50	33	Class A	0.83	•	•	Low	•	•
1773M	600 x 1200 x 15mm						•	•		•	•	
1851	2' x 4' x 5/8"	▭	0.50	35	Fire Guard	0.83	•	•	Low	•	•	
1851M	600 x 1200 x 15mm						•	•		•	•	
1796	20" x 5' x 3/4"	▭	0.50	35	Class A	0.83	S	•	Low	•	•	
1796M	500 x 1500 x 19mm						•	•		•	•	
1798	30" x 30" x 3/4"	□	0.50	35	Class A	0.83	S	•	Low	•	•	
1798M	750 x 750 x 19mm						•	•		•	•	

S = Standard

Suspension Systems

15/16"	Standard: Prelude®	Fire Guard™: Prelude XL Fire Guard
--------	--------------------	------------------------------------

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification

Type III, Form 2, Pattern C E Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

No-Added/Low Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

Low Formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information

See warranty details at armstrong.com/warranty

Weight; Square Feet/Carton

1772 – 0.94 lbs/SF; 64 SF/ctn
1773 – 0.88 lbs/SF; 80 SF/ctn
1796 – 1.33 lbs/SF; 67 SF/ctn
1798 – 1.14 lbs/SF; 60 SF/ctn
1850 – 1.19 lbs/SF; 48 SF/ctn
1851 – 1.22 lbs/SF; 64 SF/ctn