

# FINE FISSURED™ Open Plan

Square Lay-in & Tegular  
medium texture



Fine Fissured Open Plan with Suprafine® 9/16" Exposed Tee grid; Axiom® Classic Trim

## Key Selection Attributes

- Excellent solution in mixed (open plan/closed plan) office design
- Excellent combination of acoustical performance; Articulation Class (180), NRC (0.75) and CAC 35
- 30-Year Limited System Warranty against visible sag (excludes items 1755, 1757, 1759), mold/mildew and bacterial growth
- Non-directional visual reduces installation time and scrap

## Typical Applications

- Open plan offices
- Healthcare – assists in addressing HIPAA requirements
- Classrooms
- Libraries/media centers
- Lobbies/reception areas
- Computer rooms

## Detail



FINE FISSURED Open Plan



FINE FISSURED Open Plan with SUPRAFINE 9/16" Exposed Tee grid

## Color



White (WH)



# FINE FISSURED™ Open Plan

Square Lay-in & Tegular  
medium texture

Recycled Content: **72%**

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	LEED for Schools	
✓	✓	✓	✓	✓	✓	Acoustics	Low Emitting or CHPS
Location Dependent						✓	✓

\$\$\$\$\$

## Visual Selection

## Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified Acoustics			Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program	
			NRC	AC	CAC								
<b>FINE FISSURED Open Plan</b>													
15/16" Square Lay-in	1754	2' x 2' x 7/8"	□	0.75	180	35	Class A	0.86	HumiGuard+	BioBlock+	No Added	S	Yes
	1754M	600 x 600 x 22mm	●	●	●	●	●	●	●	●	●	●	●
9/16" Beveled Tegular	1755	2' x 4' x 7/8"	□	0.75	180	35	Class A	0.86	S	●	No Added	S	●
	1755M	600 x 1200 x 22mm	●	●	●	●	●	●	●	●	●	●	●
15/16" Angled Tegular	1756	2' x 2' x 7/8"	□	0.75	180	35	Class A	0.86	●	●	No Added	S	●
	1756M	600 x 600 x 22mm	●	●	●	●	●	●	●	●	●	●	●
9/16" Beveled Tegular	1758	2' x 2' x 7/8"	□	0.75	180	35♦	Class A	0.86	●	●	No Added	S	●
	1758M	600 x 600 x 22mm	●	●	●	●	●	●	●	●	●	●	●
15/16" Angled Tegular	1759	2' x 4' x 7/8"	□	0.75	180	35	Class A	0.86	S	●	No Added	S	●
	1759M	600 x 1200 x 22mm	●	●	●	●	●	●	●	●	●	●	●
15/16" Angled Tegular	1757	2' x 4' x 7/8"	□	0.75	180	35	Class A	0.86	S	●	No Added	S	●
	1757M	600 x 1200 x 22mm	●	●	●	●	●	●	●	●	●	●	●

S = Standard  
♦ 1758-CAC 33 on 9/16" Interlude, Sonata, Suprafine

## Suspension Systems

9/16"	Standard: Interlude®, Silhouette® Bolt-Slot, Sonata™, Suprafine®, Trimlok® Screw-Slot
15/16"	Standard: Prelude®

## Physical Data

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied latex paint

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

### ASTM E1264 Classification

Type III, Form 1, Pattern C E  
Fire Class A

### Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

### No-Added Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

### Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

### Insulation Value

R Factor – 2.3 (BTU units)  
R Factor – 0.40 (Watts units)

### Backloading Recommendation

Contact TechLine for specific information

### 30-Year Performance Guarantee & Warranty Information

See warranty details at [armstrong.com/warranty](http://armstrong.com/warranty)

### Weight; Square Feet/Carton

1754, 1756, 1758 – 1.08 lbs/SF; 40 SF/ctn  
1755, 1757, 1759 – 1.08 lbs/SF; 48 SF/ctn

TechLine™ / 1 877 ARMSTRONG  
1 877 276 7876

[armstrong.com/ceilings](http://armstrong.com/ceilings) (search: fine fissured)

CS-3047-109

© AWI Licensing Company, 2009 • Printed in the United States of America

