

GEORGIAN™

Square Lay-in & Tegular
medium texture



Georgian Beveled Tegular with Prelude® 15/16" Exposed Tee grid

Key Selection Attributes

- Unique painted visual
- Excellent sound absorption (items 795, 796, 1750)
- 30-Year Limited System Warranty against visible sag (excludes item 791), mold/mildew and bacterial growth

High Washability

- Durable – Washable
- Impact-resistant
- Scratch-resistant
- Scrubbable
- Meets USDA/FSIS guidelines for use in food processing establishments

Typical Applications

- Schools/classrooms
- Healthcare – assists in addressing HIPAA requirements
- Corridors/conference rooms
- Kitchen/food preparation (Items 793, 794, 828)
- Enclosed parking garages (Items 793, 794, 828)


Detail



GEORGIAN
Beveled Tegular



GEORGIAN
Beveled Tegular with
PRELUDE 15/16"
Exposed Tee grid



GEORGIAN
Beveled Tegular with
SILHOUETTE® 9/16"
Bolt-Slot 1/4" Reveal grid

Color



White (WH)

GEORGIAN™

Square Lay-in & Tegular
medium texture

Recycled Content: 39-51% Fire Guard 49%

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓		✓
Location Dependent							

\$\$\$\$\$

Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified	Acoustics		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable			Recycle Program													
				NRC	CAC						Wash	Scrub	Impact Scratch														
GEORGIAN																											
9/16" Beveled Tegular	1753	2' x 2' x 5/8"	□	0.55	35♦	Class A	0.86	HumiGuard+	BioBlock+	Low	Wash	Scrub	Impact	Scratch	Yes												
	1753M	600 x 600 x 15mm																									
15/16" Square Lay-in	764	2' x 2' x 5/8"	□	0.55	33	Class A	0.86	•	•	•	Low	•	•	•	•												
	764M	600 x 600 x 15mm																									
	763	2' x 4' x 5/8"														□	0.55	33	Class A	0.86	•	•	•	Low	•	•	•
	763M	600 x 1200 x 15mm																									
898	2' x 4' x 5/8"	□	0.55	35	Fire Guard	0.86	•	•	•	Low	•	•	•	•													
15/16" Beveled Tegular	1752	2' x 2' x 5/8"	□	0.55	35	Class A	0.86	•	•	•	Low	•	•	•	•												
	1752M	600 x 600 x 15mm																									
GEORGIAN – High Acoustics																											
15/16" Square Lay-in	796	2' x 2' x 3/4"	□	0.65	35	Class A	0.86	•	•	•	No Added	•	•	•	•												
	796M	600 x 600 x 19mm																									
15/16" Angled Tegular	1750	2' x 2' x 3/4"	□	0.65	38	Class A	0.86	•	•	•	No Added	•	•	•	•												
	1750M	600 x 600 x 19mm																									
GEORGIAN – High Washability, Unperforated																											
15/16" Square Lay-in	794	2' x 2' x 5/8"	□	N/A	33	Class A	0.88	•	•	•	Low	•	•	•	•												
	794M	600 x 600 x 15mm																									
	793	2' x 4' x 5/8"														□	N/A	33	Class A	0.88	•	•	•	Low	•	•	•
793M	600 x 1200 x 15mm																										
828	2' x 4' x 5/8"	□	N/A	35	Fire Guard	0.88	•	•	•	Low	•	•	•	•													

S = Standard

♦ 1753-CAC 33 on 9/16 Interlude, Sonata, Suprafine

Suspension Systems

9/16" Standard: Interlude®, Silhouette® Bolt-Slot, Sonata™, Suprafine®, Trimlok® Screw-Slot

15/16" Standard: Prelude® Fire Guard™: Prelude XL Fire Guard

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

793, 794, 828: factory-applied vinyl latex paint
All other items: factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)
Fire Guard: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification

Type III, Form 2, Pattern C E
Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

No-Added/Low Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

Low formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor - 1.6 (BTU units)
R Factor - 0.28 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

30-Year Performance Guarantee and Warranty Information

See warranty details at armstrong.com/warranty

Weight: Square Feet/Carton

763, 793 – 0.67 lbs/SF; 96 SF/ctn
764, 794, 1752, 1753 – 0.72 lbs/SF; 64 SF/ctn
791 – 0.76 lbs/SF; 75 SF/ctn
828, 898 – 1.13 lbs/SF; 64 SF/ctn
796, 1750 – 1.31 lbs/SF; 48 SF/ctn
795 – 1.38 lbs/SF; 64 SF/ctn

TechLine™ / 1 877 ARMSTRONG

1 877 276 7876

armstrong.com/ceilings (search: georgian)

CS-3031-109

© AWI Licensing Company, 2009 • Printed in the United States of America

