

GRAPHIS® Rustex™

Grooved Plank, Linear Beveled, Cubic Beveled
fine texture



Graphis Rustex Cubic Beveled with Suprafine® 9/16" Exposed Tee grid



Graphis Rustex Linear Beveled with Suprafine 9/16" Exposed Tee grid

Key Selection Attributes

- Bold geometric designs
- Good sound absorption
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth

Typical Applications

- Department stores/retail
- Airports/bus/train stations
- Many types of commercial interiors

Note: Not recommended for areas requiring acoustical performance

Color Selection Due to printing limitations, shade may vary from actual product.



White (WH)



Cream (CR)



Haze (HA)




Camel (CM)




Platinum (PL)

Colored ceilings are dye-lotted and should be segregated by dye lot. Do not mix.


Detail



GRAPHIS Rustex Grooved Plank



GRAPHIS Rustex Cubic Beveled



GRAPHIS Rustex Linear Beveled



GRAPHIS Rustex Cubic Beveled with SUPRAFINE 9/16" Exposed Tee grid



GRAPHIS® Rustex™

Grooved Plank, Linear Beveled, Cubic Beveled
fine texture

Recycled Content: 66%

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	LEED for Schools	
✓	✓	✓	✓	✓		Acoustics	Low Emitting or CHPS
			Location Dependent				✓

\$\$\$\$\$

Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program
			Acoustics NRC	CAC							
Grooved Plank*											
9/16" Beveled Tegular	2625 2625M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.55 30	Class A	0.75	HumiGuard+ ●	BioBlock+ ●	Low	S	Yes ●
Cubic Beveled*											
9/16" Beveled Tegular	2600 2600M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.55 30	Class A	0.75	●	●	Low	S	●
15/16" Beveled Tegular	2600 2600M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.55 30	Class A	0.75	●	●	Low	S	●
Linear Beveled*											
9/16" Beveled Tegular	2602 2602M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.55 30	Class A	0.75	●	●	Low	S	●
15/16" Beveled Tegular	2602 2602M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.55 30	Class A	0.75	●	●	Low	S	●

S = Standard

* Ceiling design copyrighted by AWI Licensing Co.

Suspension Systems

9/16"	Standard: Suprafine® XL
15/16"	Standard: Prelude®

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Type III, Form 2, Pattern J Z
Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Low Formaldehyde

Low Formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor - 1.6 (BTU units)
R Factor - 0.28 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

Warranty Information

See warranty details at armstrong.com/warranty

Application Considerations

This product is not recommended for areas requiring acoustical performance.

Weight; Square Feet/Carton

0.90 lbs/SF; 48 SF/ctn

TechLine™ / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: graphis)
CS-4018-109

© AWI Licensing Company, 2009 • Printed in the United States of America

