

OPTIMA® Open Plan – Plank

Square Lay-in & Tegular
fine texture



Optima Open Plan Plank with Interlude® XL 9/16" grid

Key Selection Attributes

- Sag-resistant large format acoustical planks
- Smooth, clean durable finish – Washable, Impact-resistant Scratch-resistant, Soil-resistant
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth
- Energy-saving high light-reflective finish
- Non-directional visual reduces installation time and scrap
- Smaller size panels available (1 carton min. order). Info: armstrong.com/specials

Typical Applications

- Open plan areas
- Corridors (walls-to-deck)
- Lobbies/reception areas (walls-to-deck)
- Areas with indirect lighting

Detail



OPTIMA Open Plan
Square Tegular



OPTIMA Open Plan
Square Lay-in
with PRELUDE® 15/16"
Exposed Tee grid

Color



White (WH)

OPTIMA® Open Plan – Plank

Square Lay-in & Tegular

fine texture

Recycled Content: **82%**

armstrong.com/greengenie



LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓	✓	✓
Location Dependent							

\$\$\$\$\$

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified			Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable			Recycle Program
			Acoustics NRC	AC	CAC						Wash	Impact	Scratch	
OPTIMA† Open Plan – Plank														
9/16" Square Tegular 	NEW 3265	2' x 5' x 1"	0.95	190	N/A	Class A	0.90	HumiGuard+	Inherent	Low	•	•	•	•
	3261	2' x 6' x 1"	0.95	190	N/A	Class A	0.90	•	•	Low	•	•	•	•
	3262	2' x 8' x 1"	0.95	190	N/A	Class A	0.90	•	•	Low	•	•	•	•
15/16" Square Lay-in 	NEW 3164	2' x 5' x 3/4"	0.90	180	N/A	Class A	0.90	•	•	Low	•	•	•	•
	3161	2' x 6' x 3/4"	0.90	180	N/A	Class A	0.90	•	•	Low	•	•	•	•
	3162	2' x 8' x 3/4"	0.90	180	N/A	Class A	0.90	•	•	Low	•	•	•	•



† U.S. Patent 6,103,360

CAC backing available on all panels as a special order

Suspension Systems

9/16"	Standard: Interlude®, Silhouette® Bolt-Slot, Suprafine®
15/16"	Standard: Prelude®

Accessories (ordered separately)

Item # 435 	Stabilizer Clip (3/4" & 1") Recommended for panels 5' and greater in length Note: Panels 5' up to 8' – One clip installed near the mid-point of each long edge. Panels 8' and over – Two clips installed at one-third points of each long edge.
7870 	Spring Border Clip (For installations with the panel resting on the wall molding)

Physical Data

Material
Fiberglass with DuraBrite® acoustically transparent membrane

Surface Finish
DuraBrite with factory-applied acrylic latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
Type XII, Form 2, Pattern E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Low Formaldehyde
Low formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

Anti Mold/Mildew & Bacteria
Fiberglass substrate is inherently resistant to the growth of mold, mildew and bacteria.

Insulation Value
3161, 3162, 3164 –
R Factor – 3.0 (BTU units)
R Factor – 0.53 (Watts units)
3261, 3262, 3265 –
R Factor – 4.0 (BTU units)
R Factor – 0.70 (Watts units)

Backloading Recommendation
Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information
See warranty details at armstrong.com/warranty

Weight; Square Feet/Carton
3161 – 0.43 lbs/SF; 96 SF/ctn
3164 – 0.43 lbs/SF; 100 SF/ctn
3162 – 0.42 lbs/SF; 128 SF/ctn
3265 – 0.50 lbs/SF; 100 SF/ctn
3261 – 0.54 lbs/SF; 72 SF/ctn
3262 – 0.54 lbs/SF; 96 SF/ctn

TechLineSM / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: optima)
CS-3682-509

LEED® is a registered trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates
© 2009 AWI Licensing Company • Printed in the United States of America

