

RANDOM FISSURED™

Vinyl-faced
Square Lay-in
fine texture

Recycled Content: **82%**

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓	✓	✓

Location Dependent

LEED for Schools

\$\$\$\$\$



Random Fissured with Prelude® 15/16" Exposed Tee grid

Key Selection Attributes

- Excellent sound absorption (perforated options)
- Easy-clean, durable surface
- Economical
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth

Typical Applications

- Discount/grocery stores
- Locker rooms
- Utility rooms
- Lavatories/restrooms

Color



White (WH)

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified	Acoustics		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable			Recycle Program
				NRC	CAC						Wash	Scrub	Impact	
RANDOM FISSURED Perforated														
15/16" Square Lay-in	2908	2' x 2' x 5/8"	□	0.70	N/A	Class A	0.72	HumiGuard+	Inherent	Low	•	•	•	–
	2908M	600 x 600 x 15mm	□	•	•	•	•	•	•	•	•	•	•	•
15/16" Square Lay-in	2910	2' x 4' x 5/8"	□	0.70	N/A	Class A	0.72	•	•	Low	•	•	•	–
	2910M	600 x 1200 x 15mm	□	•	•	•	•	•	•	•	•	•	•	•
RANDOM FISSURED Unperforated														
15/16" Square Lay-in	2909	2' x 2' x 5/8"	□	0.55	N/A	Class A	0.72	•	•	Low	•	•	•	–
	2909M	600 x 600 x 15mm	□	•	•	•	•	•	•	•	•	•	•	•
15/16" Square Lay-in	2911	2' x 4' x 5/8"	□	0.55	N/A	Class A	0.72	•	•	Low	•	•	•	–
	2911M	600 x 1200 x 15mm	□	•	•	•	•	•	•	•	•	•	•	•

Suspension Systems

15/16" Standard: Prelude®

Physical Data

Material
Fiberglass

Surface Finish
Scrubable vinyl film facing (UV protected)

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
2908, 2910 – Type XII, Form 1, Pattern E C
2909, 2911 – Type XII, Form 1, Pattern E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Low Formaldehyde
Low formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

Anti Mold/Mildew & Bacteria
Fiberglass substrate is inherently resistant to the growth of mold, mildew and bacteria.

Insulation Value
R Factor - 2.6 (BTU units)
R Factor - 0.46 (Watts units)

Backloading Recommendation
Backloading is not recommended

30-Year Performance Guarantee & Warranty Information
See warranty details at armstrong.com/warranty

Application Considerations
Not recommended for cold storage rooms less than 40° F (4° C), labs with concentration of fumes, pools, and areas where temperatures exceed 140° F (49° C)

Weight; Square Feet/Carton
0.17 lbs/SF; 128 SF/carton

TechLine™ / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: random fissured)

CS-3696-509

LEED® is a registered trademark of the U.S. Green Building Council
All other trademarks herein are the property of AWI Licensing Company and/or its affiliates
© 2009 AWI Licensing Company • Printed in the United States of America

