

# TUNDRA®

Square Lay-in & Tegular  
medium texture

Recycled Content: 33% Fire Guard 49%

## LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓		✓
Location Dependent							

LEED for Schools  
\$\$\$\$\$



Tundra with Suprafine® 9/16" Exposed Tee grid

## Key Selection Attributes

- Durable
  - Impact-resistant
  - Scratch-resistant
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth

## Typical Applications

- Offices
- Schools
- Corridors

## Color



White (WH)

## Visual Selection

## Performance Selection

Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable		Recycle Program	
			Acoustics NRC	CAC						Impact	Scratch		
<b>TUNDRA</b>													
9/16" Beveled Tegular	304	2' x 2' x 5/8"	□	0.50	33♦	Class A	0.87	HumiGuard+	BioBlock+	Low	Impact	Scratch	Yes
	304M	600 x 600 x 15mm					•	•	•		•	•	•
15/16" Square Lay-in	301	2' x 2' x 5/8"	□	0.50	33	Class A	0.87			Low			
	301M	600 x 600 x 15mm					•				•	•	•
	839	2' x 2' x 5/8"	□	0.50	33	Fire Guard	0.87			Low			
	839M	600 x 600 x 15mm					•				•	•	•
15/16" Beveled Tegular	302	2' x 4' x 5/8"	▭	0.50	35	Class A	0.87			Low			
	302M	600 x 1200 x 15mm					•				•	•	•
	840	2' x 4' x 5/8"	▭	0.50	35	Fire Guard	0.87			Low			
	840M	600 x 1200 x 15mm					•				•	•	•
15/16" Beveled Tegular	303	2' x 2' x 5/8"	□	0.50	33	Class A	0.87			Low			
	303M	600 x 600 x 15mm					•				•	•	•
15/16" Beveled Tegular	305	2' x 4' x 5/8"	▭	0.50	35	Class A	0.87			Low			
	305M	600 x 1200 x 15mm					•				•	•	•

♦ 304-CAC 31 on 9/16" Interlude, Sonata, Suprafine

## Suspension Systems

9/16" Standard: Interlude®, Sonata™, Silhouette® Bolt-Slot, Suprafine®, Trimlok® Screw-Slot

15/16" Standard: Prelude® Fire Guard™: Prelude XL Fire Guard

## Physical Data

### Material

Wet-formed high density mineral fiber

### Surface Finish

Factory-applied latex paint with scuff-resistant spatter coat

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard: A fire resistive ceiling when used in applicable UL assemblies

### ASTM E1264 Classification

Type III, Form 2, Pattern C E Fire Class A

### Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

### Low Formaldehyde

Low formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 01350.

### Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of

mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

### Insulation Value

R Factor – 1.7 (BTU units)  
R Factor – 0.30 (Watts units)

### Backloading Recommendation

Contact TechLine for specific information

### 30-Year Performance Guarantee and Warranty Information

See warranty details at [armstrong.com/warranty](http://armstrong.com/warranty)

### Weight; Square Feet/Carton

301, 302, 305 – 1.09 lbs/SF; 64 SF/ctn  
303, 304 – 1.10 lbs/SF; 48 SF/ctn  
839, 840 – 1.16 lbs/SF; 64 SF/ctn

TechLine™ / 1 877 ARMSTRONG  
1 877 276 7876

[armstrong.com/ceilings](http://armstrong.com/ceilings) (search: tundra)  
CS-3038-109

