

# ULTIMA® Open Plan

Tegular  
fine texture



Ultima Open Plan Beveled Tegular with Suprafine® 9/16" Exposed Tee grid; Axiom® Classic Trim



Ultima Open Plan Beveled Tegular with Sonata™ 9/16" Dimensional Tee grid; Axiom Classic Trim

## Key Selection Attributes

- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Excellent combination of acoustical performance, Articulation Class (170), NRC (0.75) and CAC 35
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth
- Non-directional visual reduces installation time and scrap


## Typical Applications

- Open plan offices
- Healthcare – assists in addressing HIPAA requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail
- Open plenum areas (in acoustical clouds, ex. Formations)


## Detail



ULTIMA Open Plan Beveled Tegular



ULTIMA with SUPRAFINE 9/16" Exposed Tee grid



ULTIMA with SILHOUETTE® XL 9/16" Bolt-Slot 1/4" Reveal

## Color



White (WH)

# ULTIMA® Open Plan

Tegular  
fine texture

Recycled Content: 70-80%

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	LEED for Schools	
✓	✓	✓	✓	✓	✓	Acoustics	Low Emitting or CHPS
Location Dependent						✓	✓

\$\$\$\$\$

## Visual Selection

## Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified			Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable				Recycle Program	
			Acoustics NRC	AC	CAC						Wash	Impact	Scratch	Soil		
<b>ULTIMA<sup>+</sup> Open Plan</b>																
9/16" Beveled Tegular	1942	2' x 2' x 3/4"	□	0.75	170	35*	Class A	0.89	HumiGuard+	BioBlock+	No Added	Wash	Impact	Scratch	Soil	Yes
	1942M	600 x 600 x 19mm		•	•			•	•	•		•	•	•	•	•
15/16" Beveled Tegular	1945	2' x 4' x 3/4"	□	0.75	170	35	Class A	0.89			No Added					
	1945M	600 x 1200 x 19mm		•	•			•	•			•	•	•	•	•
15/16" Beveled Tegular	1941	2' x 2' x 3/4"	□	0.75	170	35	Class A	0.89			No Added					
	1941M	600 x 600 x 19mm		•	•			•	•			•	•	•	•	•
15/16" Beveled Tegular	1944	2' x 4' x 3/4"	□	0.75	170	35	Class A	0.89			No Added					
	1944M	600 x 1200 x 19mm		•	•			•	•			•	•	•	•	•

† US Patent 5,674,594  
• 1942-CAC 33 on 9/16" Interlude, Sonata, Suprafine

## Suspension Systems

9/16"	Standard: Interlude®, Silhouette® Bolt-Slot, Sonata™, Suprafine®, Trimlok® Screw-Slot
15/16"	Standard: Prelude®

## Physical Data

### Material

Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

### Surface Finish

DuraBrite with factory-applied acrylic latex paint

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

### ASTM E1264 Classification

Type IV, Form 2, Pattern E  
Fire Class A

### Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

### No-Added Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

### Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

### Insulation Value

R Factor – 2.2 (BTU units)  
R Factor – 0.39 (Watts units)

### Backloading Recommendation

Contact TechLine for specific information

### 30-Year Performance Guarantee & Warranty Information

See warranty details at [armstrong.com/warranty](http://armstrong.com/warranty)

### Weight; Square Feet/Carton

1.14 lbs/SF; 48 SF/ctn

TechLine<sup>SM</sup> / 1 877 ARMSTRONG  
1 877 276 7876

[armstrong.com/ceilings](http://armstrong.com/ceilings) (search: ultima)  
CS-3570-109

© AWI Licensing Company, 2009 • Printed in the United States of America

