



Ultima Plank with Prelude® 15/16" Exposed Tee grid; Axiom® Classic Trim; Drywall Grid Soffit

Key Selection Attributes

- The only monolithic mineral fiber plank option
- Smooth, clean, durable finish – Washable, Scratch-resistant, Soil-resistant
- Excellent sound absorption
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth
- Visual coordinates with Optima® for mixed (open/closed plan) applications
- Energy-saving, high light-reflective finish
- Compatible with the TECHZONE™ Ceiling Systems (Items 1980, 1981, 1982 only)
- 65% pre-consumer and 15% post-consumer recycled content


Typical Applications

- Offices
- Healthcare – assists in addressing HIPAA requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail


Detail



ULTIMA Plank
Lay-in



ULTIMA Plank
Beveled Tegular



ULTIMA Plank
Shiplap Long Edge/
Beveled Tegular Short Edge



ULTIMA Plank
Shiplap Long Edge/
K2C2 Short Edge



ULTIMA Plank
Square Lay-in
with PRELUDE 15/16"
Exposed Tee grid



ULTIMA Plank
Beveled Tegular
with SUPRAFINE® 9/16"
Exposed Tee grid



ULTIMA Plank
Shiplap with
PRELUDE 15/16"
Exposed Tee grid

Color



White (WH)

ULTIMA® Plank

Lay-in, Tegular, Shiplap

fine texture

Recycled Content: **80%**

LEED® Credits

LEED® Credits						LEED for Schools	
Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	Acoustics	Low Emitting or CHPS
✓	✓	✓	✓	✓	✓	✓	✓
Location Dependent							

\$\$\$\$\$

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable				Recycle Program	
			Acoustics NRC	CAC						Wash	Impact	Scratch	Soil		
ULTIMA† Plank Lay-in															
15/16" Square Lay-in	1980	2' x 6' x 3/4"		0.70	35	Class A	0.90	HumiGuard+	BioBlock+	No Added	Wash	Impact	Scratch	Soil	Yes
	1984	2' x 5' x 3/4"		0.70	35	Class A	0.90			No Added					
ULTIMA† Plank Tegular															
9/16" Beveled Tegular	1982	2' x 6' x 3/4"		0.70	35	Class A	0.90			No Added					
	1986	2' x 5' x 3/4"		0.70	35	Class A	0.90			No Added					
15/16" Beveled Tegular	1981	2' x 6' x 3/4"		0.70	35	Class A	0.90			No Added					
	1985	2' x 5' x 3/4"		0.70	35	Class A	0.90			No Added					
ULTIMA† Plank Shiplap															
SL2 Long/K2C2 Short	1983	2' x 6' x 3/4"		0.70	35	Class A	0.90			No Added					
	1987	2' x 5' x 3/4"		0.70	35	Class A	0.90			No Added					
SL2 Long/Bev Teg Short	1988	2' x 6' x 3/4"		0.70	35	Class A	0.90			No Added					
	1989	2' x 5' x 3/4"		0.70	35	Class A	0.90			No Added					

† US Patent 5,674,594

Suspension Systems

9/16"	Standard: Interlude®, Silhouette® Bolt-Slot, Sonata™, Suprafine®, Trimlok® Screw-Slot
15/16"	Standard: Prelude®

Physical Data

Material

Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

Surface Finish

DuraBrite with factory-applied acrylic latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Type IV, Form 2, Pattern E, Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

No-Added Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperforms CHPS Section 01350 requirements. (Independent test reports available upon request.)

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information

See warranty details at armstrong.com/warranty

Weight: Square Feet/Carton

1980, 1981, 1982, 1983, 1988 – 1.08 lbs/SF; 72 SF/ctn
1984, 1985, 1986, 1987, 1989 – 1.08 lbs/SF; 80 SF/ctn

TechLineSM / 1 877 ARMSTRONG

1 877 276 7876

armstrong.com/ceilings (search: ultima)

CS-3977-109

© AWI Licensing Company, 2009 • Printed in the United States of America

