

ULTIMA[®] Themes[™] **NEW**

Blooms, Bubbles, Dragonflies, Stars
Tegular, Vector[®] fine texture



TOP: Ultima Themes Blooms 2' x 2' with Prelude[®] 15/16" Exposed Tee grid, 4-panel and single panel designs
BOTTOM: Ultima Themes Stars 2' x 2' with Prelude 15/16" Exposed Tee grid

TOP: Ultima Themes Dragonflies 2' x 2' with Silhouette[®] 9/16" grid, 4-panel and single panel designs
BOTTOM: Ultima Themes Bubbles Tegular 2' x 2' on Silhouette 9/16" grid

Key Selection Attributes

- A variety of subtle, artistic images on Ultima fine texture
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Excellent sound absorption
- 30-Year Limited System Warranty against visible sag, mold/mildew and bacterial growth
- Visual coordinates with OPTIMA[®] for mixed (open/closed plan) applications


Typical Applications

- Healthcare – assists in addressing HIPAA requirements
- Hospitality
- Department stores/retail
- Lobbies/reception areas
- Classrooms
- Offices


Detail




ULTIMA Themes Beveled Tegular



ULTIMA Themes Beveled Tegular with SUPRAFINE[®] 9/16" Exposed Tee grid



ULTIMA Themes with SILHOUETTE XL 9/16" Bolt-Slot 1/4" Reveal



ULTIMA Themes Vector



ULTIMA Themes Vector with PRELUDE 15/16" Exposed Tee grid

Color



White (WH)

ULTIMA[®] Themes[™]

Blooms, Bubbles, Dragonflies, Stars
Tegular, Vector[®] fine texture

Recycled Content: **70-71%^{**}**

armstrong.com/greengenie

LEED[®] Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✓	✓	✓	✓	✓	✓

Location Dependent

LEED for Schools






Acoustics	Low Emitting or CHPS
✓	✓

^{**} Items 1911, 1912 also available with High Recycled Content as Special Order

\$\$\$\$\$

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.*	Dimensions	UL Classified	Acoustics NRC CAC	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable					Recycle Program
										Wash	Impact	Scratch	Soil	Scrub	
ULTIMA[†] Themes Tegular															
9/16" Beveled Tegular	 Z1912A	2' x 2' x 3/4" Single panel designs 4' x 4' x 3/4" Four-panel designs		0.70 35 [♦]	Class A	0.90	HumiGuard+	BioBlock+	No Added	•	•	•	•	•	•
15/16" Beveled Tegular	 Z1911A	2' x 2' x 3/4" Single panel designs 4' x 4' x 3/4" Four-panel designs		0.70 35	Class A	0.90	•	•	No Added	•	•	•	•	•	•
ULTIMA[†] Themes Vector															
15/16" Vector	 Z1920A	2' x 2' x 3/4" Single panel designs 4' x 4' x 3/4" Four-panel designs		0.70 33	Class A	0.90	•	•	Low	•	•	•	•	•	•

† US Patents 5,674,594, 6,103,306, 6,108,994, 6,230,463
♦ Z1912A-CAC 33 on 9/16" Interlude, Sonata, Suprafine
* When specifying or ordering, include the appropriate 3-digit design suffix (e.g., Z1912AQ22)












Suspension Systems – Tegular

9/16"	Standard: Interlude [®] , Silhouette [®] Bolt-Slot, Sonata [™] , Suprafine [®] , Trimlok [®] Screw-Slot
15/16"	Standard: Prelude [®]

Suspension Systems – Vector

15/16"	Standard: Prelude
--------	-------------------

Face View Drawings – Images printed grayscale as shown. Contact your Armstrong Rep for details.

ULTIMA Themes Blooms		ULTIMA Themes Dragonflies		ULTIMA Themes Stars			ULTIMA Themes Bubbles			ULTIMA
2' x 2'	4' x 4'	2' x 2'	4' x 4'	2' x 2'	2' x 2'	2' x 2'	2' x 2'	2' x 2'	2' x 2'	2' x 2'
										
Single Panel Item 021	4-Panel Design Item 022 (Add A,B,C or D for individual panel order)	Single Panel Item 051	4-Panel Design Item 052 (Add A,B,C or D for individual panel order)	Single Panel Item 041	Single Panel Item 042	Single Panel Item 043	Single Panel Item 011	Single Panel Item 012	Single Panel Item 013	Plain Panel Tegular, Vector Item 1911 Item 1912 Item 1920

Physical Data

Material
Wet-formed mineral fiber with DuraBrite[®] acoustically transparent membrane

Surface Finish
DuraBrite with factory-applied acrylic latex paint with solvent free ultraviolet ink

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
Type IV, Form 2, Pattern E
Fire Class A

Sag Resistance
HumiGuard[®] Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

No-Added Formaldehyde
No-added formaldehyde – free of formaldehyde-based resins. Outperforms CHPS Section 01350 requirements. (Independent test reports available upon request.)

Anti-Mold/Mildew & Bacteria
BioBlock[®] Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value
R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)

Backloading Recommendation
Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information
See warranty details at armstrong.com/warranty

Weight; Square Feet/Carton
Z1911A, Z1912A – 1.05 lbs/SF; 16 SF/ctn
Z1920A – 1.08 lbs/SF; 16 SF/ctn

TechLineSM / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: ultima)
CS-4110-809

LEED[®] is a registered trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates
© 2009 AWI Licensing Company • Printed in the United States of America

